

SAFETY DATA SHEET

UNFILLED EPOXY RESIN 1448A

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: UNFILLED EPOXY RESIN 1448A

PART No.: EER1448A

SUPPLIER: H K WENTWORTH PTY LIMITED
P.O. BOX 339
BROOKVALE, NSW 2100
AUSTRALIA
Tel: 02 9938 1566
Fax: 02 9938 1566

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
CAS No.: NEOPENTYL GLYCOL DIGLYCIDYL ETHER 17557-23-2	241-536-7	Xi R-38, 43	10-30 %
Polypropylene glycol diepoxide resin 41638-13-5		Xi ,N R-36/38, 43, 52/53	10-30 %
EPOXY RESIN (Number average MW <= 700) 25068-38-6	500-033-5	Xi ,N R-36/38, 43, 51/53	30-60 %

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

HAZARDOUS SUBSTANCE: DANGEROUS GOODS

4. FIRST AID MEASURES:

INHALATION: Move the exposed person to fresh air at once.

INGESTION: DO NOT INDUCE VOMITING! Get medical attention immediately! Rinse nose, mouth and throat with water.

SKIN: Remove affected person from source of contamination. Rinse the skin immediately with lots of water. Get medical attention promptly if symptoms occur after washing.

EYES: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA: Fire can be extinguished using: Foam. Alcohol resistant foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES:

Use water to keep fire exposed containers cool and disperse vapours.

6. ACCIDENTAL RELEASE MEASURES:**SPILL CLEANUP METHODS:**

Keep combustibles away from spilled material. Stop leak if possible without risk. DO NOT touch spilled material! Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7. HANDLING AND STORAGE:**USAGE PRECAUTIONS:**

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame.

STORAGE PRECAUTIONS:

Keep in cool, dry, ventilated storage and closed containers. Keep in original container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:**INGREDIENT COMMENTS:**

OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT:**VENTILATION:**

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

RESPIRATORS:

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL).

PROTECTIVE GLOVES:

Use protective gloves.

EYE PROTECTION:

Use approved safety goggles or face shield.

OTHER PROTECTION:

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENIC WORK PRACTICES:

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. No eating or drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES:**APPEARANCE:**

Viscous. Liquid.

COLOUR:

Black.

BOILING POINT (°C, interval):

>200

Pressure:**DENSITY/SPECIFIC GRAVITY (g/ml):**

1.05 - 1.10

Temperature (°C):

21-23

VISCOSITY (interval):

200 - 350 mPas

Temperature (°C):

21-23

SOLUBILITY DESCRIPTION:

Insoluble in water.

10. STABILITY AND REACTIVITY:

STABILITY:	Normally stable.
CONDITIONS TO AVOID:	Avoid contact with acids and oxidising substances.
HAZARDOUS DECOMP. PRODUCTS:	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂). Nitrous gases (NO _x).

11. TOXICOLOGICAL INFORMATION:


INHALATION:	May cause irritation to the respiratory system.
INGESTION:	May cause discomfort if swallowed. May cause stomach pain or vomiting.
SKIN:	Irritating to skin. May cause sensitisation by skin contact. May cause allergic contact eczema. Prolonged or repeated contact leads to drying of skin. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.
EYES:	Irritating to eyes. May cause chemical eye burns.
ROUTE OF ENTRY:	Inhalation. Ingestion. Skin and/or eye contact.

12. ECOLOGICAL INFORMATION:

ECOLOGICAL INFORMATION:	Dangerous for the environment if discharged into watercourses.
--------------------------------	--

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS:	Dispose of in accordance with Local Authority requirements.
--------------------------	---

14. TRANSPORT INFORMATION:**LABEL FOR CONVEYANCE:**

UN No. ROAD:	3082
UK ROAD TRANSPORT CLASS:	9
UK ROAD PACK GR.:	III
ADR CLASS No.:	9
ADR CLASS:	Class 9: Miscellaneous dangerous substances and articles.
ADR ITEM No.:	III
ADR MARGINAL:	2901
ADR LABEL No.:	9

HAZCHEM CODE:	2X
CEFIC TEC(R) No.:	90GM6-III
PROPER SHIPPING NAME I:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))
RID CLASS No.:	9
RID ITEM No.:	III
UN No. SEA:	3082
IMDG CLASS:	9
IMDG PACK GR.:	III
EmS No.:	None
MFAG TABLE No.:	See Guide
MARINE POLLUTANT:	No.
UN No., AIR:	3082
ICAO CLASS:	9
AIR PACK GR.:	III

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



RISK PHRASES:	R-36/38 Irritating to eyes and skin. R-43 May cause sensitisation by skin contact. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
SAFETY PHRASES:	S-24/25 Avoid contact with skin and eyes. S-26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S-37 Wear suitable gloves.
STATUTORY INSTRUMENTS:	Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

USER NOTES:	CN No 39073000
REVISION COMMENTS:	Revised in accordance with CHIP3 and EU Directive 1999/45/EC
ISSUED BY:	Helen O'Reilly
REVISION DATE:	SEPT 2003
REV. No./REPL. SDS GENERATED:	1
SDS No.:	10653

DISCLAIMER:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification

R-PHRASES (Full Text):

R-36/38 Irritating to eyes and skin. R-43 May cause sensitisation by skin contact. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-38 Irritating to skin. R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.