10-30 %

60-100 %

SAFETY DATA SHEET SURFACE MOUNT ADHESIVE

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: SURFACE MOUNT ADHESIVE

PART No.: ESMA10SL

SUPPLIER: H K WENTWORTH PTY LIMITED

P.O. BOX 339

BROOKVALE, NSW 2100

AUSTRALIA Tel: 02 9938 1566 Fax: 02 9938 1566

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME CONTENT

CAS No.: EINECS Nr.: CLASSIFICATION

NEOPENTYL GLYCOL DIGLYCIDYL ETHER

17557-23-2 241-536-7 Xi R-38, 43

EPOXY RESIN (Number average MW <= 700)

25068-38-6 500-033-5 Xi ,N R-36/38, 43, 51/53

Aliphatic Amines 10-30 %

Xi R-36/37

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

HAZARDOUS SUBSTANCE: DANGEROUS GOODS

4. FIRST AID MEASURES:

INHALATION: Move the exposed person to fresh air at once. Keep the affected person warm and at

rest. Get prompt medical attention.

INGESTION: DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT

OR DRINK FLUIDS! Rinse mouth thoroughly. Promptly get affected personnel to drink

large volumes of water to dilute the swallowed chemical. Get medical attention

immediately! Provide rest, warmth and fresh air.

SKIN: Remove affected person from source of contamination. Get medical attention promptly

if symptoms occur after washing. Rinse the skin immediately with lots of water. Get

medical attention if any discomfort continues.

EYES: Remove victim immediately from source of exposure. Make sure to remove any contact

lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA: Fire can be extinguished using: Foam. Alcohol resistant foam. Dry chemicals, sand,

dolomite etc.

SPECIAL FIRE FIGHTING

PROCEDURES:

Use water to keep fire exposed containers cool and disperse vapours.

6. ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS: Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

Keep combustibles away from spilled material. Stop leak if possible without risk. DO NOT touch spilled material! Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage. Runoff or release to sewer, waterway or ground is forbidden. Inform

Authorities if large amounts are involved.

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame.

STORAGE PRECAUTIONS: Keep in cool, dry, ventilated storage and closed containers. Keep in original container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT COMMENTS: OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT:







VENTILATION:No specific ventilation requirements noted, except this product must not be used in a

confined space without good ventilation.

RESPIRATORS: No specific recommendation made, but respiratory protection must be used if the

general level exceeds the Occupational Exposure Level (OEL).

PROTECTIVE GLOVES: Use protective gloves.

EYE PROTECTION: Use approved safety goggles or face shield.

OTHER PROTECTION: Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENIC WORK PRACTICES: DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before

eating, smoking and using the toilet. Wash promptly if skin becomes wet or

contaminated. Promptly remove any clothing that becomes contaminated. No eating or

drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Paste or slurry.

COLOUR: Red.

BOILING POINT (°C, interval): >200 Pressure:

DENSITY/SPECIFIC GRAVITY 1.18 Temperature (°C): 20

(g/ml):

VISCOSITY (interval): 1450 mPas Temperature (°C): 20

SOLUBILITY DESCRIPTION: Insoluble in water.

10. STABILITY AND REACTIVITY:

STABILITY: Normally stable.

CONDITIONS TO AVOID: Avoid contact with acids and oxidising substances.

HAZARDOUS DECOMP. Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

PRODUCTS: Nitrous gases (NOx).

11. TOXICOLOGICAL INFORMATION:

HEALTH WARNINGS: INGESTION.

May cause stomach pain or vomiting. Pulmonary sensitizer.

SKIN CONTACT.

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause sensitisation by skin contact. This chemical may cause skin/eye irritation and burns

(corrosive). May cause skin irritation/eczema.

INHALATION.

Severe pulmonary irritant. May cause irritation to the respiratory system.

EYE CONTACT.

May cause severe irritation to eyes. EYES, NOSE AND MOUTH. Repeated exposure may cause chronic eye irritation. SKIN. Mild dermatitis, allergic skin rash. Defatting,

drying and cracking of skin.

ROUTE OF ENTRY: Inhalation. Ingestion. Skin and/or eye contact.

TARGET ORGANS: Eyes. Gastro-intestinal tract. Respiratory system, lungs. Skin.

MEDICAL SYMPTOMS: Severe pulmonary irritation. General respiratory distress, unproductive cough. Nausea,

vomiting.

12. ECOLOGICAL INFORMATION:

ECOLOGICAL INFORMATION: Dangerous for the environment if discharged into watercourses.

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS: Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION:

LABEL FOR CONVEYANCE:



UN No. ROAD: 3082

UK ROAD TRANSPORT CLASS: 9

UK ROAD PACK GR.: III
ADR CLASS No.: 9

ADR CLASS: Class 9: Miscellaneous dangerous substances and articles.

ADR ITEM No.:

ADR MARGINAL: 2901
ADR LABEL No.: 9

HAZCHEM CODE: 2X

CEFIC TEC(R) No.: 90GM6-III

PROPER SHIPPING NAME I: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN

(Number average MW <= 700))

RID CLASS No.:

RID ITEM No.:

UN No. SEA: 3082

IMDG CLASS: 9

IMDG PACK GR.:

EmS No.: F-A; S-F

MFAG TABLE No.: See Guide

MARINE POLLUTANT: No.

UN No., AIR: 3082

ICAO CLASS: 9

AIR PACK GR.:

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:





RISK PHRASES: R-36/38 Irritating to eyes and skin.

R-43 May cause sensitisation by skin contact.

R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

SAFETY PHRASES: P-5 Contains epoxy constituents. See information supplied by the manufacturer.

S-2 Keep out of reach of children.

S-24/25 Avoid contact with skin and eyes.

S-26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S-29/56 Do not empty into drains, dispose of this material and its container to

hazardous or special waste collection point.

S-37 Wear suitable gloves.

S-46 If swallowed seek medical advice immediately and show this container label. S-61 Avoid release to the environment. Refer to special instructions/ Safety Data

Sheets.

STATUTORY INSTRUMENTS: Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE: Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES: Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation

HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

USER NOTES: CN No 39073000

REVISION COMMENTS: Revised in accordance with CHIP3 and EU Directive 1999/45/EC

ISSUED BY: Helen O'Reilly

REVISION DATE: MAY 2003

REV. No./REPL. SDS GENERATED: 0

SDS No.: 10623

DISCLAIMER: This information relates only to the specific material designated and may not be valid

for such material used in combination with any other materials or in any process unless specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or

quality specification

R-PHRASES (Full Text): R-36/38 Irritating to eyes and skin. R-43 May cause sensitisation by skin contact.

R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-38 Irritating to skin. R-36/37 Irritating to eyes and respiratory

system.