

Solvent Cleaning		CCC	DGC	FRC	IPA	ECSP	ULS	FLU	ULC	MDS	SSS	SSW
		Non-Flammable Cleaner	Non-Flammable Degreaser	Non-Flammable Flux Remover	Isopropyl Alcohol	ECS Plus	Ultrasolve	Fluxclene	Ultraclens	Metal Degreasing Solvent	Screen & Stencil Solvent	Screen & Stencil Wipes
Typical Properties	Density (g/ml)	1.37	1.33	1.33	0.8	0.8	0.8	0.8	0.8	1.32	1.025	0.851
	Flashpoint (°C IP- 34)	None	None	None	12	-48	0	0	>60*	None	>60*	>60*
	Boiling Point (°C IP- 123)	45	36	36	82	36	>80	>80	>173	40	>100	>100
	Vapour Pressure (kPa) D2889	34.7	66.2	66.2	4.4	53.3	11.5	11.5	0.5	47.5	1.45	1.5
	Evaporation rate (ether = 1)	1.1	>1	>1	6	1.5	16	16	66	6	>50	33
	TLV (ppm)	242	242	242	400	500	300	300	300	100	300	300
Soil Removal	Heavy Grease	Yes	Best	Yes	Yes	Yes	Yes	Yes	Yes	Best	Yes	Yes
	Ionic	Yes	Yes	Yes	Yes	Yes	Best	Yes	Yes	No	Yes	Yes
	Flux	Yes	Yes	Best	Yes	Yes	Yes	Best	Yes	Yes	Yes	Yes
Plastics Compatibility	ABS	Test	Test	Test	Yes	Yes	Test	Test	Test	No	No	No
	Polymethacrylate (acrylic)	Test	Test	Test	Yes	Test	Test	Test	Test	No	Test	Test
	Polycarbonate	Test	Test	Test	Yes	Yes	No	No	Yes	No	No	Test
	Polystyrene	Test	Test	Test	Yes	Yes	Test	No	Test	No	No	No

Evaporation Rate: The higher the number the slower the rate of evaporation.

Many solvents do not affect plastics on short contact times (spray and wipe) but may be unsuitable for prolonged immersion.

*Classified as non-flammable.

Disclaimer: All information is given in good faith but without warranty.