



XXLS 12" Subwoofer



Type Number: 830845

Features:

This new series of state-of-the-art subwoofers continue to enhance Peerless' reputation for delivering the highest quality components for bass in the world. Called the XXLS - for "Xpanded Extra Long Stroke" - these new audio transducers add even more excursion to the Peerless XLS line, and completely eliminate distortion.

Driver Highlights: Thick Nomex cone, 51 mm voice coil, ALP

[Go to Application Notes.](#)



Specs:

Electrical Data

Nominal impedance	Zn	8	ohm
Minimum impedance	Zmin	6.7	ohm
Maximum impedance	Zo	126.7	ohm
DC resistance	Re	5.9	ohm
Voice coil inductance	Le	3.6	mH
Capacitor in series with x ohm	Cc	--	uF

T-S Parameters

Resonance Frequency	fs	21.5	Hz
Mechanical Q factor	Qms	9.68	
Electrical Q factor	Qes	0.47	
Total Q factor	Qts	0.45	
Ratio fs/Qts	F	48	
Force factor	Bl	13.1	Tm
Mechanical resistance	Rms	1.41	Kg/s
Moving mass	Mms	101.4	g
Suspension compliance	Cms	0.54	mm/N
Effective cone diameter	D	24.4	cm
Effective piston area	Sd	466	cm ²
Equivalent volume	Vas	162.5	ltrs
Sensitivity		88	dB
Ratio BL/√(Re)		5.4	


Power handling

100h RMS noise test (IEC)	175	W
Long-term Max System Power (IEC)	350	W
Max linear SPL (rms) @ power	--	dB/W
Short Term Max power	--	W

Voice Coil and Magnet Parameters

Voice coil diameter	51	mm
Voice coil height	33	mm
Voice coil layers	4	
Height of the gap	8	mm
Linear excursion +/-	12.5	mm
Max mech. excursion +/-	--	mm
Flux density of gap	--	mWb
Total useful flux	2.3	mWb
Diameter of magnet	147	mm
Height of magnet	35	mm
Weight of magnet	2.4	Kg

Frequency:



Mechanical Dimensions:

