



## ***SRT 5023X***

- **PVR Functions via USB External Mass Storage Device**
- **Record & Playback**
- **USB 2.0 Host for Video & MP3 Playback, JPEG Viewing and Firmware Update**
- **Super Sensitive Tuner**
  
- **Digital Audio: S/PDIF RCA**
- **Component Video: Y/Pb/Pr RCA**
- **Super Video: 4 Pin Mini Din**
- **CVBS + L/R Audio RCA**
- **16:9 Full Screen, 4:3 Letterbox & Full Screen**
- **Auto & Manual Search Mode**
- **Favourite Channel List Editing**
- **Picture in Menu & Zoom**
- **EPG - Electronic Program Guide**
- **Captions & Teletext (Does NOT require Teletext capable TV)**
- **Signal / Quality Level Indicator**
- **8 Timer Event Settings**
- **Parental Lock**
- **Password Change Option**
- **RS-232C Port for Software Updates**
- **Games**
- **DVB/T Compliant**
- **COFDM Demodulation**

## **DIGITAL TERRESTRIAL TELEVISION RECEIVER**



 **STRONG**

[www.strong-technologies.com](http://www.strong-technologies.com)

*not just by name*

# **STRONG SRT 5023X SPECIFICATIONS**



## TUNER

Guard Interval Modes	: 1/32, 1/16, 1/8, 1/4 Active Symbol Duration
FEC Mode Rates	: 1/2, 2/3, 3/4, 5/6, 7/8
Input Connector	: IEC 169-2, Female
Frequency Range	: 176-860MHz
Demodulator	: COFDM 2K/8K-Carrier
Channel Bandwidth	: 6/7/8MHz Switchable by Software (7MHz for Australia)

## MPEG TS A/V Decoder

Video Resolution	: 720 x 576, 720 x 480	Audio Decoding	: MPEG/Musical Layer 1 & 2
Audio Mode	: Single / Dual Channel	Input Bit Rate	: Max. 90 Mbit/s
Transport Stream	: MPEG-2 ISO/IEC 13818-1		

## A/V & Data Input/Output

Video	: RCA/Cinch Y, Pb, Pr (Component) : RCA/Cinch (CVBS) : 4 Pin Mini Din Connector - S-Video
Audio	: RCA/Cinch L/R with Volume & Mute Control (2 pairs) : Resolution: 20 bits DAC, Max 2 Vrms : S/PDIF for Dolby Digital and MPEG-2 Bit Stream Out
RS-232C	: Transfer Rate 115Kbps, 9 PIN D-Sub Type
USB 2.0	: Video File Type : *.MPG, *.DAT, *.VOB, *.AVI, *.Xvid & *.DivX (4.0 / 5.0) : Audio File Type : *.MP3 & *.WAV : Picture File Type : *.JPEG

## System Resources

Flash Memory	: 2Mbyte
SDRAM	: 16Mbyte
Main CPU MPEG Chip	: SPHE1002


## Power Supply

Input Voltage	: AC 100 to 240V	Power Consumption	: Max. 15 W
Protection	: Separate Internal Fuse	Type	: Switch Mode Power Supply

## Physical Specifications

Size (W x H x D)	: 250 x 38 x 175 (case) 185 (end of connectors) mm	E. & O. E.
Net Weight	: 1.9 Kg	
Operating Temperature	: 0°C ~ 50°C	

## DISTRIBUTED BY:



**STRONG TECHNOLOGIES PTY LTD. - 60 Wedgewood Road, Hallam, Victoria 3803, Australia**  
**Phone: +61 3 8795-7990 - Fax: +61 3 8795-7991 - Technical Support: 1800 820 030**  
**www.strong-technologies.com - salesau@strong-technologies.com**