

# Color Dome Camera

## MTC-808AD

1/3" Hi-Res. Color Dome Camera  
Built-in Auto Iris Lens

## MTC-805AD

1/3" Med-Res. Color Dome Camera  
Built-in Auto Iris Lens



## SPECIFICATIONS

	MTC-808AD		MTC-805AD	
TV System	PAL	NTSC	PAL	NTSC
Image Sensor	1/3" SONY Super HAD CCD			
Number of Total Pixels	795(H) X 596(V)	811(H) X 508(V)	537(H) X 597(V)	537(H) X 505(V)
Synchronizing System	Internal			
Resolution	480 TVL		420 TVL	
Minimum Illumination	0.15Lux@F1.4		0.1Lux@F1.4	
Signal to Noise Ratio	More than 48dB(AGC Off)			
Automatic Gain Control	ON/OFF (Switchable)			
F.L(Flickerless)	ON/OFF (Switchable)			
AES	ON/OFF (Switchable)			
Back Light Compensation	ON/OFF (Switchable)			
DC Level	The VR for adjusting the IRIS level of auto IRIS lens.			
White Balance	2500°k~9200°k			
Video Output	1Vp-p Composite / 75 Ω			
Lens/Angle of View(H)	Standard:f4.0mm /F1.4 Auto Iris Lens /67° Option:f2.9, 6.0, 8.0mm/ F1.4 Auto Iris Lens / 88°, 47.5°, 36.5°			
Power Supply	Standard:12Vcd; Option:12Vdc/24Vac			
Power Consumption	2.5W		1.8W	
Operation Temperature	-10°C~+50°C			
Operation Humidity	RH85% or less			
Storage Temperature	-20°C ~ +60°C			
Dimensions	118(DIA) x 88(H)mm			
Weight	12Vcd:380g; 12Vdc/24Vac:450g			

## DIMENSIONS

