

SAFETY DATA SHEET

ANTI-STATIC FOAM CLEANSER

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: ANTI-STATIC FOAM CLEANSER

PART No.: EAFC200/400D

SUPPLIER: H K WENTWORTH PTY LIMITED
P.O. BOX 339
BROOKVALE, NSW 2100
AUSTRALIA
Tel: 02 9938 1566
Fax: 02 9938 1566

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
CAS No.: PROPAN-2-OL 67-63-0	200-661-7	Xi ,F R-11, 36, 67	1-5 %
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSENE - UNSPECIFIED 64742-47-8	265-149-8	Xn R-65	1-5 %
Alkylbenzene sulphonic acid 68081-81-2		Xn R-22, 38, 41	1-5 %
2-BUTOXYETHANOL 111-76-2	203-905-0	Xn R-20/21/22, 36/38	1-5 %
BUTANE 106-97-8	203-448-7	Fx R-12	1-5 %

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Not regarded as a health or environmental hazard under current legislation.

4. FIRST AID MEASURES:

INHALATION: Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION: DO NOT INDUCE VOMITING! Rinse mouth thoroughly.

SKIN: Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYES: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA:	This material is not flammable. Use extinguishing media appropriate for surrounding fire.
SPECIAL FIRE FIGHTING PROCEDURES:	Move container from fire area if it can be done without risk.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Aerosol cans may explode in fires.

6. ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS:	Absorb in vermiculite, dry sand or earth and place into containers.
-------------------------------	---

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS:	Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
STORAGE PRECAUTIONS:	Store at moderate temperatures in dry, well ventilated area.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
PROPAN-2-OL	67-63-0	OES	400 ppm	500 ppm
2-BUTOXYETHANOL	111-76-2	OES	25 ppm(Sk)	50 ppm(Sk)
BUTANE	106-97-8	OES	600 ppm	750 ppm
VENTILATION:	No particular ventilation requirements.			
OTHER PROTECTION:	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.			
HYGIENIC WORK PRACTICES:	Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin. No eating or drinking while working with this material. DO NOT SMOKE IN WORK AREA!			

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE:	Aerosol. Liquid.		
COLOUR:	Colourless.		
ODOUR/TASTE:	Characteristic.		
BOILING POINT (°C, interval):	>100	Pressure:	
DENSITY/SPECIFIC GRAVITY (g/ml):	0.995	Temperature (°C):	20
VAPOUR PRESSURE:	2.35 kPa	Temperature (°C):	20
VOLATILITY DESCRIPTION:	Volatile.		
pH-VALUE, CONC. SOLUTION:	7-8		
SOLUBILITY DESCRIPTION:	Insoluble in water.		

10. STABILITY AND REACTIVITY:

CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalies.
HAZARDOUS DECOMP. PRODUCTS:	Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. TOXICOLOGICAL INFORMATION:

HEALTH HAZARDS, GENERAL:	No specific health warnings noted.
INHALATION:	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.
SKIN:	Contact with liquid form may cause frostbite.
OTHER HEALTH EFFECTS:	This substance has no evidence of carcinogenic properties.

12. ECOLOGICAL INFORMATION:

ECOLOGICAL INFORMATION:	Not regarded as dangerous for the environment.
--------------------------------	--

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS:	Empty containers must not be burned because of explosion hazard. Dispose of in accordance with Local Authority requirements.
--------------------------	--

14. TRANSPORT INFORMATION:

LABEL FOR CONVEYANCE:



UN No. ROAD:	1950
UK ROAD TRANSPORT CLASS:	2.2
UK ROAD PACK GR.:	Not Applicable
ADR CLASS No.:	2.2
ADR CLASS:	Division 2.2: Nonflammable, nontoxic gases.
ADR ITEM No.:	Not Applicable
ADR MARGINAL:	2201
ADR LABEL No.:	2.2
CEFIC TEC(R) No.:	20G5A,20G50
PROPER SHIPPING NAME I:	AEROSOLS
RID CLASS No.:	2.2
RID ITEM No.:	Not Applicable
UN No. SEA:	1950

IMDG CLASS:	2.2
IMDG PAGE No.:	9022
IMDG PACK GR.:	Not Applicable
EmS No.:	F-D; S-U
MFAG TABLE No.:	See Guide
MARINE POLLUTANT:	No.
UN No., AIR:	1950
ICAO CLASS:	2.2
AIR PACK GR.:	Not Applicable

15. REGULATORY INFORMATION:

NC Not classified

RISK PHRASES:	Not classified.
SAFETY PHRASES:	SPECIAL PROVISIONS ON THE LABELLING OF AEROSOL DISPENSERS. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep out of the reach of children. X % by mass of the content are flammable.
UK REGULATORY REFERENCES:	Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972. Chemicals (Hazard Information & Packaging) Regulations 1993.
ENVIRONMENTAL LISTING:	Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.
EU DIRECTIVES:	System of specific information relating to Dangerous Preparations. 91\155. Dangerous Preparations Directive 88\379.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

USER NOTES:	CN No 34029010
REVISION COMMENTS:	Revised in accordance with CHIP3 and EU Directive 1999/45/EC
ISSUED BY:	Helen O'Reilly
REVISION DATE:	MAY 2003
REV. No./REPL. SDS GENERATED:	0
SDS No.:	10241
DISCLAIMER:	This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification
R-PHRASES (Full Text):	R-11 Highly flammable. R-36 Irritating to eyes. R-67 Vapours may cause drowsiness and dizziness. R-65 Harmful: may cause lung damage if swallowed. R-22 Harmful if swallowed. R-38 Irritating to skin. R-41 Risk of serious damage to eyes. R-20/21/22 Harmful by inhalation, in contact with skin and if swallowed. R-36/38 Irritating to eyes and skin. R-12 Extremely flammable.