

SAFETY DATA SHEET

METAL PRIMER

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: METAL PRIMER

PART No.: OP9018

SUPPLIER: H K WENTWORTH PTY LIMITED
P.O. BOX 339
BROOKVALE, NSW 2100
AUSTRALIA
Tel: 02 9938 1566
Fax: 02 9938 1566

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
CAS No.: XYLENE 1330-20-7	215-535-7	Xn R-10, 20/21, 38	10-30 %
BUTANONE 78-93-3	201-159-0	Xi ,F R-11, 36, 66, 67	30-60 %
EPOXY RESIN (Number average MW <= 700) 25068-38-6	500-033-5	Xi ,N R-36/38, 43, 51/53	10-30 %
2-METHOXY-1-METHYLETHYL ACETATE 108-65-6	203-603-9	Xi R-10, 36	1-5 %
ETHYLBENZENE 100-41-4	202-849-4	Xn ,F ,N R-11, 20, 51/53	1-5 %

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Highly flammable. Harmful by inhalation and in contact with skin. Irritating to eyes and skin. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

HAZARDOUS SUBSTANCE: DANGEROUS GOODS

4. FIRST AID MEASURES:

INHALATION: Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION: DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Promptly get affected personnel to drink large volumes of water to dilute the swallowed chemical. Get medical attention immediately!

SKIN: Rinse the skin immediately with lots of water. Get medical attention if any discomfort continues.

EYES: Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while

lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA:	Fire can be extinguished using: Foam. Alcohol resistant foam. Dry chemicals, sand, dolomite etc.
SPECIAL FIRE FIGHTING PROCEDURES:	Use water to keep fire exposed containers cool and disperse vapours.

6. ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS:	Absorb in vermiculite, dry sand or earth and place into containers. Wear necessary protective equipment. Wash thoroughly after dealing with a spillage.
-------------------------------	---

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS:	Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame.
STORAGE PRECAUTIONS:	Keep in cool, dry, ventilated storage and closed containers. Keep in original container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
ETHYLBENZENE	100-41-4	OES	100 ppm(Sk)	125 ppm(Sk)
XYLENE	1330-20-7	OES	50 ppm(Sk)	100 ppm(Sk)
BUTANONE	78-93-3	OES	200 ppm(Sk)	300 ppm(Sk)

INGREDIENT COMMENTS: OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT:



VENTILATION:	Provide adequate general and local exhaust ventilation.
RESPIRATORS:	No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL).
PROTECTIVE GLOVES:	Use protective gloves.
EYE PROTECTION:	Use approved safety goggles or face shield.
OTHER PROTECTION:	Wear appropriate clothing to prevent any possibility of skin contact.
HYGIENIC WORK PRACTICES:	DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. No eating or drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE:	Viscous. Liquid.
COLOUR:	Blue.
ODOUR/TASTE:	Solvent.

BOILING POINT (°C, interval):	80	Pressure:	
DENSITY/SPECIFIC GRAVITY (g/ml):	0.900	Temperature (°C):	20
VISCOSITY (interval):	250 mPas	Temperature (°C):	20
SOLUBILITY DESCRIPTION:	Immiscible with water.		
FLASH POINT (°C):	5	Method:	CC (Closed cup).

10. STABILITY AND REACTIVITY:

STABILITY:	Normally stable.
CONDITIONS TO AVOID:	Avoid contact with acids and oxidising substances.
HAZARDOUS DECOMP. PRODUCTS:	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂). Nitrous gases (NO _x).

11. TOXICOLOGICAL INFORMATION:

INHALATION:	Harmful by inhalation. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.
INGESTION:	May cause stomach pain or vomiting.
SKIN:	Harmful in contact with skin. May cause sensitisation by skin contact. May cause allergic contact eczema.
EYES:	Irritating to eyes.
HEALTH WARNINGS:	EYES, NOSE AND MOUTH. Repeated exposure may cause chronic eye irritation. SKIN. Mild dermatitis, allergic skin rash. Defatting, drying and cracking of skin.
ROUTE OF ENTRY:	Ingestion. Skin and/or eye contact.

12. ECOLOGICAL INFORMATION:

LC 50, 96 HRS, FISH mg/l:	1.2
EC 50, 48 HRS, DAPHNIA, mg/l:	2.7
IC 50, 72 HRS, ALGAE, mg/l:	9.4
ECOLOGICAL INFORMATION:	Dangerous for the environment if discharged into watercourses.

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS:	Dispose of in accordance with Local Authority requirements.
--------------------------	---

14. TRANSPORT INFORMATION:

LABEL FOR CONVEYANCE:



UN No. ROAD:	1993
UK ROAD TRANSPORT CLASS:	3
UK ROAD PACK GR.:	II
ADR CLASS No.:	3
ADR CLASS:	Class 3: Flammable liquids.
ADR ITEM No.:	II
ADR LABEL No.:	3
HAZCHEM CODE:	3YE
CEFIC TEC(R) No.:	30GF1-I+II,30GF1-sp
PROPER SHIPPING NAME I:	FLAMMABLE LIQUID, N.O.S. (BUTANONE, XYLENE)
RID CLASS No.:	3
RID ITEM No.:	II
UN No. SEA:	1993
IMDG CLASS:	3
IMDG PACK GR.:	II
EmS No.:	F-E; S-E
MFAG TABLE No.:	See Guide
MARINE POLLUTANT:	No.
UN No., AIR:	1993
ICAO CLASS:	3
AIR PACK GR.:	II

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



RISK PHRASES:

R-11 Highly flammable.
 R-20/21 Harmful by inhalation and in contact with skin.
 R-36/38 Irritating to eyes and skin.
 R-43 May cause sensitisation by skin contact.
 R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES:

S-16 Keep away from sources of ignition - No Smoking.
 S-24/25 Avoid contact with skin and eyes.
 S-36/37 Wear suitable protective clothing and gloves.
 S-51 Use only in well ventilated areas.

STATUTORY INSTRUMENTS:	Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

USER NOTES:	CN NO 32082010
REVISION COMMENTS:	Revised in accordance with CHIP3 and EU Directive 1999/45/EC
ISSUED BY:	Helen O'Reilly
REVISION DATE:	MAY 2003
REV. No./REPL. SDS GENERATED:	0
SDS No.:	10243
DISCLAIMER:	This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification
R-PHRASES (Full Text):	R-11 Highly flammable. R-20 Harmful by inhalation. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-10 Flammable. R-20/21 Harmful by inhalation and in contact with skin. R-38 Irritating to skin. R-36 Irritating to eyes. R-66 Repeated exposure may cause skin dryness or cracking. R-67 Vapours may cause drowsiness and dizziness. R-36/38 Irritating to eyes and skin. R-43 May cause sensitisation by skin contact.