

SAFETY DATA SHEET

GALVANISING SPRAY - MATT

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: GALVANISING SPRAY - MATT

PART No.: EPGM400

SUPPLIER: H K WENTWORTH PTY LIMITED
P.O. BOX 339
BROOKVALE, NSW 2100
AUSTRALIA
Tel: 02 9938 1566
Fax: 02 9938 1566

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME			CONTENT
CAS No.:	EINECS Nr.:	CLASSIFICATION	
n-HEPTANE 142-82-5	205-562-2	Xn ,F ,N R-11, 38, 50/53, 65, 67	1-5 %
HEXANE MIXTURE OF ISOMERS (MAX 5% n-HEXANE (203-777-6))		Xn ,F ,N R-11, 38, 51/53, 65, 67	1-5 %
TOLUENE 108-88-3	203-625-9	Xn ,F R-11, 20	1-5 %
XYLENE 1330-20-7	215-535-7	Xn R-10, 20/21, 38	1-5 %
1,2,4-TRIMETHYLBENZENE 95-63-6	202-436-9	Xn ,N R-10, 20, 36/37/38, 51/53	1-5 %
ETHYL ACETATE 141-78-6	205-500-4	Xi ,F R-11, 36, 66, 67	1-5 %
BUTANE 106-97-8	203-448-7	Fx R-12	30-60 %
DIMETHYL ETHER 115-10-6	204-065-8	Fx R-12	10-30 %
HYDROCARBON DISTILLATE 64742-82-1	265-185-4	Xn ,N R-10, 51/53, 65	1-5 %
CYCLOHEXANE 110-82-7	203-806-2	Xn ,F ,N R-11, 38, 50/53, 65, 67	5-10 %

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Extremely flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DANGEROUS GOODS: NON HAZARDOUS SUBSTANCE.

4. FIRST AID MEASURES:

INHALATION:	Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Get medical attention.
INGESTION:	Immediately rinse mouth and provide fresh air.
SKIN:	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
EYES:	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA:	Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
SPECIAL FIRE FIGHTING PROCEDURES:	Move container from fire area if it can be done without risk.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Aerosol cans may explode in fires.

6. ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS:	Absorb in vermiculite, dry sand or earth and place into containers. Ventilate well.
-------------------------------	---

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS:	Avoid spilling, skin and eye contact. Provide good ventilation.
STORAGE PRECAUTIONS:	Store at moderate temperatures in dry, well ventilated area.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
n-HEPTANE	142-82-5	OES	500 ppm	
TOLUENE	108-88-3	OES	50 ppm(Sk)	150 ppm(Sk)
XYLENE	1330-20-7	OES	50 ppm(Sk)	100 ppm(Sk)
ETHYL ACETATE	141-78-6	OES	200 ppm	400 ppm
BUTANE	106-97-8	OES	600 ppm	750 ppm
DIMETHYL ETHER	115-10-6	OES	400 ppm	500 ppm
CYCLOHEXANE	110-82-7	OES	100 ppm	300 ppm

OTHER PROTECTION: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENIC WORK PRACTICES: Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin. No eating or drinking while working with this material. **DO NOT SMOKE IN WORK AREA!**

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE:	Aerosol. Liquid.
COLOUR:	Grey.
ODOUR/TASTE:	Characteristic.

BOILING POINT (°C, interval):	60	Pressure:	
MELT./FREEZ. POINT (°C, interval):	-130		
DENSITY/SPECIFIC GRAVITY (g/ml):	1.24	Temperature (°C):	20
BULK DENSITY:	1240 kg/m ³		
VOLATILITY DESCRIPTION:	Volatile.		
SOLUBILITY DESCRIPTION:	Immiscible with water.		
FLASH POINT (°C):	<0	Method:	CC (Closed cup).
FLAMMABILITY LIMIT - LOWER(%):	3.8		
FLAMMABILITY LIMIT - UPPER(%):	18		

10. STABILITY AND REACTIVITY:

STABILITY:	Normally stable.
CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

11. TOXICOLOGICAL INFORMATION:

INHALATION:	May cause irritation to the respiratory system. Solvent vapours are hazardous and may cause nausea, sickness and headaches. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.
SKIN:	Product has a defatting effect on skin. Prolonged or repeated contact leads to drying of skin. Prolonged or repeated exposure may cause severe irritation.
EYES:	Irritating to eyes.
OTHER HEALTH EFFECTS:	This substance has no evidence of carcinogenic properties.
ROUTE OF ENTRY:	Inhalation.

12. ECOLOGICAL INFORMATION:

ECOLOGICAL INFORMATION:	Dangerous for the environment if discharged into watercourses.
--------------------------------	--

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS:	Empty containers must not be burned because of explosion hazard. Dispose of in accordance with Local Authority requirements.
--------------------------	--

14. TRANSPORT INFORMATION:

LABEL FOR CONVEYANCE:



UN No. ROAD:	1950
UK ROAD TRANSPORT CLASS:	2.1
UK ROAD PACK GR.:	Not Applicable
ADR CLASS No.:	2.1
ADR CLASS:	Division 2.1: Flammable gases.
ADR ITEM No.:	Not Applicable
ADR MARGINAL:	2201
ADR LABEL No.:	2.1
CEFIC TEC(R) No.:	20G5F
PROPER SHIPPING NAME I:	AEROSOLS
RID CLASS No.:	2.1
RID ITEM No.:	Not Applicable
UN No. SEA:	1950
IMDG CLASS:	2.1
IMDG PACK GR.:	Not Applicable
EmS No.:	F-E; S-U
MFAG TABLE No.:	See Guide
MARINE POLLUTANT:	No.
UN No., AIR:	1950
ICAO CLASS:	2.1
AIR PACK GR.:	Not Applicable

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



RISK PHRASES:	R-12 Extremely flammable. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
SAFETY PHRASES:	S-16 Keep away from sources of ignition - No Smoking. S-51 Use only in well ventilated areas. S-9 Keep container in a well ventilated place. SPECIAL PROVISIONS ON THE LABELLING OF AEROSOL DISPENSERS. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Keep out of the reach of children.

UK REGULATORY REFERENCES:	Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972. Chemicals (Hazard Information & Packaging) Regulations 1993.
ENVIRONMENTAL LISTING:	Rivers (Prevention of Pollution) Act 1961. Control of Pollution Act 1974.
EU DIRECTIVES:	System of specific information relating to Dangerous Preparations. 91\155.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Occupational Exposure Limits EH40. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

USER NOTES:	CN No 32081090
REVISION COMMENTS:	Revised in accordance with CHIP3 and EU Directive 1999/45/EC
ISSUED BY:	Helen O'Reilly
REVISION DATE:	MAY 2003
REV. No./REPL. SDS GENERATED:	0
SDS No.:	10806
DISCLAIMER:	This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification
R-PHRASES (Full Text):	R-11 Highly flammable. R-38 Irritating to skin. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-65 Harmful: may cause lung damage if swallowed. R-67 Vapours may cause drowsiness and dizziness. R-50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-20 Harmful by inhalation. R-10 Flammable. R-20/21 Harmful by inhalation and in contact with skin. R-36/37/38 Irritating to eyes, respiratory system and skin. R-36 Irritating to eyes. R-66 Repeated exposure may cause skin dryness or cracking. R-12 Extremely flammable.